


COB LED Linear Fixture



LUXX Light Technology

ABOUT US

LUXX Lichttechnik GmbH / LUXX Light Technology Ltd. Represents a German headquartered inter-national group with lighting competence and innovations since over 20 years.

Our core competences:

- Research & Development
- Design
- Manufacturing
- Quality Assurance
- Cost Control

LUXX is dedicated to slim and energy efficient linear lighting fixtures since 1997.

1997 — CCFL (cold cathode fluorescent lamp) slim and energy efficient linear lighting fixtures

2006 — LED ultra slim and energy efficient linear lighting fixtures

2012 — All LED Commercial Lighting fixtures and replacements

2013 — LED Industrial Lighting fixtures

Since 2014 LUXX presents the latest edition:

- LED refrigeration equipment lighting, freezers, coolers, chillers, cabinets
- LED fresh food lighting—cabinets, shelves and displays
- LED vending machine lighting
- LED shelf- and rack lighting

LUXX Light Technology (Shenzhen) Ltd.

5th Floor, Building 8, Hui Debao Industrial Park, Bai Huayuan Rd, Guang Ming District Shenzhen 518107, China

Phone: +86 755 27049942

Fax: +86 755 29677724

info@luxx.cn

www.luxx.cn



CANNES

PMMA LED cooler lighting fixture

The quadrant lighting fixture can be adapted to any corner elegantly.

Different configurations available upon request.

Specifications / data per meter

Electrical

Power 9W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 120°
Efficiency 100 Lm/W
Lumen 900 Lm (clear)
800 Lm (frosted)

IP Rating IP54

Working Temperature


-25°C / -35°C to + 45°C

Appearance

Material PMMA
Dimension L1000 x W10 x H10mm
Max. Length Available 3100mm
Diffuser Clear / Frosted

Accessories

Spring steel clip (with screw/magnet), Magnetic tape



DUO CANNES

PMMA LED cooler lighting fixture

Duo Cannes can light up two sides of most refrigerators, chillers and cabinets.

Different configurations available upon request.

Specifications / data per meter

Electrical

Power 18W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 210°
Efficiency 100 Lm/W
Lumen 1800 Lm

IP Rating IP54

Working Temperature


-25°C / -35°C to + 45°C

Appearance

Material PMMA
Dimension L1000 x W18.4 x H10mm
Max. Length Available 3100mm
Diffuser Clear

Accessories

Spring steel clip (with screw/magnet), Magnetic tape





NIZZA

PMMA LED cooler lighting fixture

The co-extruded PMMA lighting fixture is designed for shelf and refrigeration display lighting. Different configurations available upon request.

Specifications / data per meter

Electrical

Power 9W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 120°
Efficiency 80 Lm/W
Lumen 700 Lm

IP Rating IP54

Working Temperature


-25°C / -35°C to + 45°C

Appearance

Material PMMA
Dimension L1000 x W11 x H12mm
Max. Length Available 3100mm
Diffuser Milky

Accessories

Spring steel clip (with screw/magnet), Magnetic tape



Magnetic Clip Screw Magnetic Tape



MONZA

PMMA LED cooler lighting fixture

A special optical diffuser makes the LED dots invisible, creating a linear effect similar to that of fluorescent tubes.

Food display versions are available.

Different configurations available upon request.

Specifications / data per meter

Electrical

Power 9W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 210°
Efficiency 60 Lm/W
Lumen 550 Lm

IP Rating IP54

Working Temperature


-25°C / -35°C to + 45°C

Appearance

Material PMMA
Dimension L1000 x W11 x H14mm
Max. Length Available 3100mm
Diffuser Milky white

Accessories

Spring steel clip (with screw/magnet), Magnetic tape



Magnetic Clip Screw Magnetic Tape



SIENA

PMMA LED cooler lighting fixture

Sienna is designed for shelf and refrigeration display lighting. Mounting is easy using metal clips or magnets. Different configurations available upon request.

Specifications / data per meter

Electrical

Power 9W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 120°
Efficiency 100 Lm/W
Lumen 900 Lm

IP Rating IP54

Working Temperature


-25°C / -35°C to + 45°C

Appearance

Material PMMA
Dimension L1000 x W17 x H8.7mm
Max. Length Available 3100mm
Diffuser Clear

Accessories

Spring steel clip (with screw/magnet), Magnetic tape



Magnetic Clip

Screw

Magnetic Tape



MANTUA

PMMA LED cooler lighting fixture

Mantua is designed for refrigeration lighting applications as an alternative to T5 tube light installations. Different configurations available upon request.

Specifications / data per meter

Electrical

Power 9W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 120°
Efficiency 100 Lm/W
Lumen 900 Lm

IP Rating IP54

Working Temperature


-25°C / -35°C to + 45°C

Appearance

Material PMMA
Dimension L1000 x Φ 16mm
Max. Length Available 3100mm
Diffuser Clear

Accessories

Spring steel clips (with screw / magnet)
PC clip (with screw / magnet)



PC clip with screw

PC clip with screw

Spring steel clip with screw

Spring steel clip with Magnet



MONACO

PMMA LED shelf lighting fixture

Our smallest lighting fixture ever, just 5mm x 7mm! Hundreds of thousands sold to the European display industry. Monaco is designed for display, cabinet and undercabinet applications. Different configurations available upon request.

Specifications / data per meter

Electrical

Power	7W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	456 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	120°
Efficiency	100 Lm/W
Lumen	700 Lm (clear) 600 Lm (frosted)

Appearance


Material	PMMA
Dimension	L1000 x W7 x H5mm
Max. Length Available	2500mm
Diffuser	Clear / Frosted

Mounting

Surface

Accessories

Spring steel clip (with screw/magnet), Adhesive tape



Screw

Magnetic Clip

Adhesive Tape



ALU MONACO Slim

PMMA LED cooler lighting fixture

An ultra slim lighting fixture, just 6mm x 8mm. Alu Monaco Slim is designed for ceiling, wall, cabinet and undercabinet applications. One of the smallest LED lighting fixtures in the world. Different configurations available upon request.

Specifications / data per meter

Electrical

Power	7W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	456 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	120°
Efficiency	100 Lm/W
Lumen	700 Lm (Clear) 500 Lm (Milky)

Appearance


Material	Anodized aluminium, PMMA
Dimension	L1000 x W8 x H6mm
Max. Length Available	2500mm
Diffuser	Clear / Frosted / Milky

Mounting

Surface / Recessed

Accessories

Spring steel clip (with screw/magnet), Adhesive tape



Magnetic Clip

Screw

Adhesive Tape

Recessed



ALU MONACO semi-linear

Another ultra small lighting fixture, just 8mm x 10mm!
This one is designed for ceiling, wall, cabinet and undercabinet applications.
Semi-linear, means the LED dots are slightly visible, Alu Monaco does not provide a completely linear light.
Different configurations available upon request.

Specifications / data per meter

Electrical

Power 7W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 456 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 90°
Efficiency 100 Lm/W
Lumen 700 Lm (Clear)
450 Lm (Milky)

Appearance



Material Anodized aluminium, PMMA
Dimension L1000 x W8 x H10mm
Max. Length Available 2500mm
Diffuser Clear / Frosted / Milky

Mounting

Surface

Accessories

Spring steel clip (with screw/magnet), Adhesive tape



ROMA

The smallest linear fixture in the world, just in 10mm x10mm. Our special lenticular diffuser creates a truly linear light without any visible LED dots.
A perfect choice, if you are looking for a small yet linear light source up to 2500mm.

Specifications / data per meter

Electrical

Power 9W
Input voltage 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 120°
Efficiency 100 Lm/W
Lumen 900 Lm (clear)
700 Lm (Milky)

Appearance


Material Anodized aluminium, PMMA
Dimension L1000 x W10 x H10mm
Max. Length Available 3100mm
Diffuser Clear/Milky

Mounting

Surface / Recessed

Accessories

Spring steel clip (with screw/magnet), Adhesive tape





SLIMLINE SM

Slimline SM is designed for shelf and refrigeration display lighting.

Mounting is easy using metal clips and magnets.

Our standard fixture for most lighting applications.

Food display versions are available.

Different configurations available upon request.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	480 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	120°
Efficiency	100 Lm/W
Lumen	900 Lm (Clear) 700 Lm (Milky)

Food Display Versions

Meat	CCT-Pink
Fish	CCT-10000K
Vegetable&Fruit	CRI>97 Ra

Appearance


Material	Anodized aluminium, PMMA
Dimension	L1000 x W17 x H8.7mm
Max. Length Available	2500mm
Diffuser	Clear / Frosted / Milky

Mounting

Surface

Accessories

Spring steel clip (with screw/magnet), Magnetic tape



Magnetic Clip

Screw

Adhesive Tape



SLIMLINE RM

Slimline RM allows a recessed, flush mounting.

It is designed for display and cabinet lighting applications.

Food display versions are available.

Different configurations available upon request.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	480 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	120°
Efficiency	90-100 Lm/W
Lumen	900 Lm (Clear) 700 Lm (Milky)

Food Display Versions

Meat	CCT-Pink
Fish	CCT-10000K
Vegetable&Fruit	CRI>97 Ra

Appearance


Material	Anodized aluminium, PMMA
Dimension	L1000 x W23.2 x H8.7mm
Max. Length Available	2500mm
Diffuser	Clear / Frosted / Milky

Mounting

Recessed



Recessed



LAS VEGAS

LAS VEGAS is a fixture which offers 5 different light beam angles (20°, (45°), (60°), (75°), (90°),

This focuses the light and creates various wall washer effects.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	480 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	Adjustable 20°, 45°, 60°, 75°, 90°
Efficiency	90 Lm/W
Lumen	800 Lm

Appearance

Material	Anodized aluminium, PMMA
Dimension	L1000 x W15.5 x H18mm
Max. Length Available	2500mm
Diffuser	Clear / Frosted / Milky

Mounting

Surface

Accessories

Spring steel clip (with screw/magnet), Adhesive tape



Magnetic Clip Screw Adhesive Tape



MONZA LINEAR

PMMA LED shelf lighting fixture

A special optical diffuser makes the LED dots invisible, creating a linear effect similar to that of fluorescent tubes.

Food display versions are available.

Different configurations available upon request.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	480 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output


Beam Angle	120°
Efficiency	60 Lm/W
Lumen	500 Lm

Appearance

Material	PMMA
Dimension	L1000 x W11 x H14mm
Max. Length Available	3100mm
Diffuser	Milky white

Accessories

Spring steel clip (with screw/magnet), Adhesive tape



Magnetic Clip Screw Adhesive Tape



NIZZA LINEAR

PMMA LED shelf lighting fixture

The co-extruded PMMA lighting fixture is designed for shelf and refrigeration display lighting. Food display versions are available. Different configurations available upon request.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	480 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	120°
Efficiency	80 Lm/W
Lumen	700 Lm

Appearance


Material	PMMA
Dimension	L1000 x W11 x H12mm
Max. Length Available	3100mm
Diffuser	Milky

Mounting

Surface

Accessories

Spring steel clip (with screw/magnet), Adhesive tape



MEMPHIS

Memphis is designed as a solid shelf lighting fixture. Several mounting options apply. Fresh food display versions and different configurations are available upon request.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	480 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	120°
Efficiency	100 Lm/W
Lumen	900 Lm (Clear) 700 Lm (Milky)

Appearance


Material	Anodized aluminium, PMMA
Dimension	L1000 x W17 x H17.8mm
Max. Length Available	2500mm
Diffuser	Clear / Frosted / Milky

Mounting

Surface

Accessories

Spring steel clip / Magnet





MIAMI

Miami is designed as a indirecting shelf lighting fixture. An ideal fixture for shelf lighting from the front. Fresh food display versions and different configurations are available upon request.

Specifications / data per meter

Electrical

Power 9W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output


Beam Angle 90°
Efficiency 80 Lm/W
Lumen 800 Lm

Appearance

Material Anodized aluminium, PC
Dimension L1000 x W22 x H12.5mm
Max. Length Available 2500mm
Diffuser Milky

Mounting

Recessed



Recessed



NAPLES

Naples is a standard indirect lighting fixture. An ideal fixture for under cabinet lighting from the front. Fresh food display versions and different configurations are available upon request.

Specifications / data per meter

Electrical

Power 9W
Input voltage 12V / 24V DC

LED

Type COB
Q'ty 480 chips
CCT 2700~6500K
CRI >80 Ra

Light Output

Beam Angle 120°
Efficiency 80 Lm/W
Lumen 800 Lm

Appearance

Material Anodized aluminium, PMMA
Dimension L1000 x W29.5 x H16.4mm
Max. Length Available 2500mm
Diffuser Milky

Mounting

Recessed



Recessed



TORINO

Torino is designed for shelf lighting applications as an alternative to T5 and T8 tube light installations. The fixture can be easily mounted -45° \ to $+45^\circ$ \ in 15° \ steps. Different configurations are available upon request.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	480 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	90°
Efficiency	100 Lm/W
Lumen	1000 Lm (Clear) 800 (Milky)

Appearance


Material	Anodized aluminium, PMMA
Dimension	L1000 x Φ 16mm
Max. Length Available	2500mm
Diffuser	Clear / Frosted / Milky

Mounting

Surface

Accessories

Spring steel clips (with screw / magnet)
PC clip (with screw / magnet)



ALU CANNES linear

A special optical diffuser makes the LED dots nearly invisible. Creating a linear effect similar to that of fluorescent tubes.

Different configurations are available upon request.

Specifications / data per meter

Electrical

Power	9W
Input voltage	12V / 24V DC

LED

Type	COB
Q'ty	456 chips
CCT	2700~6500K
CRI	>80 Ra

Light Output

Beam Angle	110°
Efficiency	50 Lm/W
Lumen	500 Lm

Appearance

Material	Anodized aluminium, PMMA
Dimension	L1000 x W10 x H10mm
Max. Length Available	2500mm
Diffuser	Milky

Mounting

Surface (especially in corners)

Accessories

Spring steel clip (with screw/magnet) / Adhesive tape

